



KEY BENEFITS:

- **Effortless integration** – Simply apply tags to metallic assets.
- **Ready adoption** – Interoperable with RAIN UHF RFID compliant devices.
- **Enhanced effectiveness** – Faster, more accurate than QR-codes or text transactions.

TECHNOLOGY HIGHLIGHTS:

- Standards compliant options RAIN UHF RFID
- Label reels may be programmed and printed using standard equipment
- Each tag guaranteed to work
- Versions for on- or off-metal use
- Peel and stick flexibility plus options to have labels supplied individually or on rolls allows simple, cost effective and efficient asset management

OTHER OPTIONS:

- Customized labels from [LUX-IDent](#)
- [HID Trusted Tag versions](#)
- [IQ Non-metal Labels](#)
- IQ Pro Labels
- [Sense Passive Tags](#)

IQ 6025

	機械仕様
周波数範囲	902-928 MHz
ICチップ	IMPINJ M730
メモリ	EPC – 128 bits User – 0 bits Unique TID - 96 bits
読取距離 Impinj R420	Up to 10.0 m – on metal Up to 6.0 m – off metal
	物理仕様
寸法	60 x 25 x 1.3(mm)
取付方法	粘着剤付き
取付素材	金属
素材	白色
重量	1.0 g
色	白
	耐久性能
保護等級	IP68
衝撃振動試験	MIL STD 810-G
	耐熱性能
保存温度範囲	-40° to +85° C
動作温度範囲	-40° to +85° C
	その他
プロトコル	EPC Class 1 Gen2v2
オプション	印字 & エンコード
保証期間	1 年



HID

www.hidglobal.com

For more information, contact china_sales@omni-id.com / chinasales.oid@hidglobal.com

© 2022 HID Global Corporation/ASSA ABLOY AB. All rights reserved.
Part of ASSA ABLOY